## For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

# WC33 7/8" OD (Copper Sweat) Water Heater Connectors

**Use:** For use in exposed locations only to connect water heaters and other water connected devices to the

water supply

### **Design Features:**



### **Operating Specifications:**

Temperature: 40° to 180° F (maximum 82° C)

**Pressure:** water pressures up to 125 PSI maximum

CONNECTOR MATERIAL SPECIFICATIONS				
Tubing	Copper			
Sleeve	Plastic			



PART DIMENSIONS (Inches)					
Connector Length (±.25)					
Model	Dim.	12"	15"	18"	24"
WC33	Α	11.25	14.25	17.25	23.25

_							
Pa	rt	•	ıc	t	ın	n	•

WC33-12	3/4" nom male sweat ( $7/8$ " OD) x $3/4$ " nom male sweat ( $7/8$ " OD) x $12$ " length
WC33-15	3/4" nom male sweat (7/8" OD) x 3/4" nom male sweat (7/8" OD) x 15" length
WC33-18	3/4" nom male sweat (7/8" OD) x 3/4" nom male sweat (7/8" OD) x 18" length
WC33-24	3/4" nom male sweat (7/8" OD) x 3/4" nom male sweat (7/8" OD) x 24" length

#### **Listings & Certifications:**

IAPMO listed to ASME A112.18.6 / CSA B125.6



